

TRSK-24A



Products Features


- Good structure stability with buckle
- Various window size
- Strong anti-saturataion ability
- Provide a variety of combined output methods
- Good linearity and high sensitive level

Application


- Online enviromental monitoring
- Smart fire-fighting power consumption
- Low voltage power distribution system
- Power quality analysis and eletrical equipment collection
- Electricity measurement

Mechanical dimension


Dimension (mm)




Front View



Side View




Bottom View



Mechanical characteristics

Aperture $\Phi 23\text{mm}$

Electrical schematic diagram





Technical data

Transformation ratio	100A/5A	125A/5A	150A/5A	200A/5A	250A/5A
Accuracy class	5.0	3.0	3.0	3.0	0.5
External load	$\leq 0.04\Omega$	$\leq 0.008\Omega$	$\leq 0.008\Omega$	$\leq 0.04\Omega$	$\leq 0.04\Omega$
Lead wire	6 $\pm$ 0.05m	4 $\pm$ 0.05m	4 $\pm$ 0.05m	6 $\pm$ 0.05m	2.5 $\pm$ 0.05m
Weight	Around 230g	Around 270g	Around 310g	Around 270g	Around 280g
Rated capacity	1VA				
Overload	1.2 times				
Frequency	50Hz/60Hz				
Inner diameter	Φ 23mm				
Tolerance	$\pm$ 1.5mm				
Power frequency withstand voltage	3kV AC/1min				
Ambient operating temperature	-25°C~+75°C	-25°C~+70°C	-25°C~+70°C	-25°C~+75°C	-25°C~+70°C
Ambient storage temperature	-40°C~+85°C	-40°C~+70°C	-40°C~+70°C	-40°C~+85°C	-40°C~+70°C

Contact information

HUBEI TIANRUI ELECTRONIC CO.,LTD.

Add: No.8 Chuangye Road, Econommic Development Zone, Tianmen 431700, Hubei, China

Website: www.trelectron.com

Email: export@hbtianrui.com