

TRSK-50A



Products Features


- Good structure stability with buckle
- Various window size
- Strong anti-saturataion ability
- Provide a variety of combined output methods
- Good linearity and high sensitive level

Application


- Online enviromental monitoring
- Smart fire-fighting power consumption
- Low voltage power distribution system
- Power quality analysis and eletrical equipment collection
- Electricity measurement

Mechanical dimension


Dimension (mm)




Front View



Side View




Bottom View



Mechanical characteristics

Aperture $\Phi 50\text{mm}$

Electrical schematic diagram





Technical data

Transformation Ratio	500A/1A	600A/1A	800A/5A	1200A/5A
External Load	$\leq 0.5\Omega$	$\leq 0.5\Omega$	$\leq 0.2\Omega$	$\leq 0.2\Omega$
Lead Wire	6 $\pm$ 0.05m	6 $\pm$ 0.05m	5 $\pm$ 0.05m	5 $\pm$ 0.05m
Weight	Around 650g	Around 680g	Around 620g	Around 980g
Accuracy Class	0.5			
Overload	1.2 times			
Frequency	50Hz/60Hz			
Inner Diameter	Φ 50mm			
Power Frequency Withstand Voltage	3kV AC/1min			
Ambient Operating Temperature	-40°C ~ 70°C	-40°C ~ 70°C	-25°C ~ +70°C	-25°C ~ +70°C
Ambient Storage Temperature	-45°C ~ 75°C	-45°C ~ 75°C	-40°C ~ +85°C	-40°C ~ +85°C

Contact information

HUBEI TIANRUI ELECTRONIC CO.,LTD.

Add: No.8 Chuangye Road, Econommic Development Zone, Tianmen 431700, Hubei, China

Website: www.trelectron.com

Email: export@hbtianrui.com